## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Design For The People

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2220526001

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					

ParameterValueParameterValueGeneral product parameters:Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer26Energy efficiency classEUseful luminous flux (\$use), in- dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)3 200 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), ex- pressed in W26,0Standby power (P_sb), expressed in W-Networked standby power (Pnet) for CLS, expressed in W and rounded to the second dec- imal-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set80							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer26Energy efficiency classEUseful luminous flux (фuse), in- dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)3 200 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), ex- pressed in W26,0Standby power (Psb), expressed in W-Networked standby power (Pnet) for CLS, expressed in W and rounded to the second dec- imal-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val-80	Parameter		Value	Parameter	Value		
mode (kWh/1000 h), rounded up to the nearest integerClassUseful luminous flux (фuse), in- dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)3 200 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), ex- pressed in W26,0Standby power (Psb), expressed in W and rounded to the sec- ond decimal-Networked standby power (Pnet) for CLS, expressed in W-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val-80	General product parameters:						
dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)Sphere (360°)temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be setOn-mode power (Pon), ex- pressed in W26,0Standby power (Psb), expressed in W and rounded to the sec- ond decimalNetworked standby power (Pnet) for CLS, expressed in W-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val-	mode (kWh/10	00 h), rounded	26		E		
pressed in W expressed in W and rounded to the sec- ond decimal   Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second dec- imal - Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val-	dicating if it refe a sphere (360 <sup>o</sup> )	ers to the flux in , in a wide cone		temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K,	3 000		
(Pnet) for CLS, expressed in W and rounded to the second dec- imaldex, rounded to the nearest integer, or the range of CRI-val-	•	ver (P <sub>on</sub> ), ex-	26,0	expressed in W and rounded to the sec-	_		
	(P <sub>net</sub> ) for CLS, e and rounded to	expressed in W	-	dex, rounded to the nearest integer, or the range of CRI-val-	80		
Outer dimen-Height117Spectral power dis-See image	Outer dimen-	Height	117	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing controlWidth400tribution in the range 250 nm to 800 nm, at full-loadin last page	separate con- trol gear, light-			range 250 nm to 800	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	0,438 0,401			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	10	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

