

Rocket

Design: Doshi Levien

Type: Curtain

Composition: 100% Trevira CS

Yarn type: Filament Construction: Warp knit

Width: Approx. 200 cm, 78,5 inches Weight: Approx. 220 g/lin.m, 7.1 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 0% when washed at 60°C.

Ironing might be necessary. Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk

Special recommendations

Knitted textiles differ from woven textiles in terms of their performance and construction. As Rocket is a warp knitted textile, we do not recommend any sewing.

To adjust the length or the width of the textile, simply cut it along the meshes. Thanks to the construction of the textile it will not fray. This also applies if the textile stretches after installation.

Use a pleating tape in the top.

If more pieces of textile are to be installed next to each other, we recommend making a $4-6\,\mathrm{cm}$ loose overlap instead of sewing them together.









Rocket

Lightfastness

Note 7 ISO 105-B02

Light Reflection DIN EN 410

4-31% (test is performed in flat state)

Light Transmission DIN EN 410

46-62% (test is performed in flat state)

Absorption

100 mm airgap 0.00/Not classified (flat), 0.05/Not classified (waved) EN ISO 354

Airflow

<10 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3

ASTM E84 Class A Unadhered

BS 5867 part 2 type B CAN ULC S102 CAN ULC S109 DIN 4102 B1 EN 13501-1, B-s1, d0 EN 13 773 class 1 GB 8624 B1

IMO FTP Code 2010 Part 5 IMO FTP Code 2010 Part 7

JIS L 1091 A-1 D NF P 92 507 M1 NFPA 701 SN 198 898 5.2 UNI 9177 Classe 1

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0 Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage ASTM D434

Not required fabric under weight



Quality benefits

Very good lightfastness Permanent flame retardant Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standards of ISO 14040 Health Product Declaration (HPD): Declaring textile content and substance

Special recommendations

When hanging, the curtain should touch the ground.

Country of origin

Portugal

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information kvadrat.dk

